## AUTOTRONIK

Fertigungssysteme für die Elektronikindustrie

#### AUTOTRONIK-SMT GmbH

Sulzbacher Str. 111 D-92224 Amberg

Tel +49 (0) 9621-600 691 Fax +49 (0) 9621-600 692

office@autotronik-smt.com www.autotronik-smt.de

## MODEL: BA385E1-V

#### **SMT-PICK&PLACE MACHINE**



- Automatic detection of loose components
- High Accuracy and high Flexibility from 01005 up to 0.3 mm fine pitch
- ▶ 128 intelligent Auto Tape Feeder w. Quick Scan Function
- Ballscrews in X-Y direction
- ▶ Up to 4.500 CPH
- COGNEX Alignment System "Vision On the Fly"
- Digital Bottom Vision Kamera for fine pitch QFP & BGA
- ▶ Automatic Reference Point Recognition w. digital camera
- Dispenser System
- Vision Inspection
- Universal CAD Conversion
- ▶ Barcode Reader for Feeder setup
- ► EtherCAT Bus System





Innovative Features



Unbeatable



Worldwide for you



Specialist in smal and medium-size manufacturing.



Quality & innovation a fair price.



All from







# MODEL: BA385E1-V

### **SMT-PICK&PLACE MACHINE**

#### **SPEZIFICATION:**

- Number of Heads (Vision on the Fly): 1
- Placement rate (under optimum condition):

4500 CPH, 3400 CPH (IPC 9850)

- Feeder capacity (8mm): up to 128 Tape Feeders
- IC Tray capacity: up to 2 Waffle Trays
- Component Sense: Vision detection
- Component Size:

Handled by digital head camera:

- smallest: 0.4 x 0.2 mm
- largest: 16 x 14 mm

Handled by fixed digital Bottom Vision Camera:

- largest: 150 x 100 mm

- Resolution:
  - X/Y Axis: 0.005 mm
  - Z Axis: 0.01 mm
- Rotation: 0° to 360° (0.09°/step)
- Placement Accuracy: +/- 0.03 mm
- X/Y Repeatability: +/- 0.01 mm
- Placement Area:

without Waffle Tray: 435 x 430 mm with 1 Waffle Tray: 435 x 270 mm

- Programming:
  - Direct Input
  - Teach-In by Camera
  - CAD Access (option)
  - Barcode Reader (option)
- Industrial PC with Windows 10

Power Supply: 230VACPower: 2400W

• Pressure: 75 psi (5.5 bar), max. 100L/min

• Machine Size: 1270 x 990 x 1355 mm (L x W x H)

• Weight: 710kg







