## **AUTOTRONIK** Fertigungssysteme für die **Elektronikindustrie**

AUTOTRONIK-SMT GmbH Sulzbacher Str. 111 D-92224 Amberg Tel +49 (0) 9621-600 691

Fax +49 (0) 9621-600 692 office@autotronik-smt.com www.autotronik-smt.de



## MODEL: HD812V6 SMT-PICK&PLACE MACHINE

- Perfect for high volume production
- High Accuracy and high Flexibility from 0402 up to 18x20mm
- 16 intelligent Auto Tape Feeder
- Ballscrew with AC Servo in X direction
- Linear Motor in Y direction
- Up to 30000 CPH
- COGNEX Alignment System with bottom camera
- Automatic Reference Point Recognition
- Conveyor System
- Vision Inspection
- Universal CAD Conversion
- Barcode Reader for Feeder setup
- Tracability of production data





Service

Features







manufacturing.



Quality 8

a fair price






Intelligent feeders in all common sizes Component spectrum from 0402 to 18x20 mm



Head design is special made for long strip LED boards, but also can handle different forms.









## **MODEL:** HD812V6 SMT-PICK&PLACE MACHINE

## **SPEZIFICATION:**

- Number of Heads (Vision on the Fly): 6 •
- Placement rate (under optimum condition): • 30000 CPH
- Feeder capacity (8mm): up to 16 Tape Feeders •
- **Component Sense: Vision detection**
- **Component Size:** 
  - Handled by fixed Bottom Vision Camera:
    - smallest: 1.0 x 0.5 mm \_
    - largest: 18 x 20 mm
- Resolution:
  - X Axis: 0.02 mm (Linear Motor) -
  - Y Axis: 0.02mm (AC Servo Motor)
  - Z Axis: 0.02 mm
- Rotation: 0° to 360° (0.09°/step)
- Placement Accuracy: +/- 0.05 mm
- Placement Area without conveyor:
  - 1200 x 300 mm \_
- Placement Area with conveyor:
  - 1200 x 300 mm
- **Programming:** 
  - **Direct Input**
  - **Teach-In by Camera** 2
  - CAD Access (option)
  - Barcode Reader (option)
  - Tracability of production data (option)
- Industrial PC with Windows 10
- Power Supply: 230VAC
- 3700W Power:
- Pressure:
  - 75 psi (5.5 bar), max. 150L/min Machine Size: 1721 x 2566 x 1885 mm (L x W x H)
- Weight: 850kg